

# COOPER® WORK SERIES™


## REGIONAL HAUL APPLICATION

GET TO WORK

The COOPER® WORK SERIES™ steer/all-position, drive and trailer tires are an on-/off-highway regional haul lineup with various fuel, scrub and chip guard compounds.


### WORK SERIES™ RHA 2

The Cooper® WORK Series™ RHA 2 tire is a 20/32" super-regional and regional all-position tire with a balanced tread compound for fuel efficiency and long miles to removal. The stone protector ledges help minimize stone retention. The scrub guard compound helps resist wear in high-scrub applications.



### WORK SERIES™ RHA

The Cooper® WORK Series™ RHA tire is a fuel-efficient regional all-position tire with a wide footprint to help maximize traction and tread depths ranging from 18/32" to 22.5/32". The tapered grooves and stone protectors help resist stone drilling. The sidewall features curb guard protection for tight turns and scrubbing.



### WORK SERIES™ ASA

The Cooper® WORK Series™ ASA tire is a 17/32" all-position tire for regional and pick-up/delivery applications. The scrub-resistant compound, all-steel construction, curb bar and stone protectors combine to help with urban last mile deliveries.



SCAN TO  
DOWNLOAD



COOPER  
TIRES

COMMERCIAL SERIES  
PRO WORK SEVERE

# COOPER® WORK SERIES™

## REGIONAL HAUL APPLICATION

### WORK SERIES™ AWD

The Cooper® WORK Series™ AWD tire is an open-shoulder, 26/32", highly siped regional drive tire for traction and long, even wear. The full-depth sipes, shoulder notches and snow groove technology help the AWD achieve 3PMSF traction requirements.



### WORK SERIES™ RHD

The Cooper® WORK Series™ RHD has a 26/32" deep open-shoulder drive tread to help maximize traction. The tread compound offers fuel efficiency and miles to removal. The sidewall features curb guard protection for tight turns.



Varies by size




### WORK SERIES™ ASD

The Cooper® WORK Series™ ASD tire is an open-shoulder drive tire for regional and pick-up/delivery that has tread depths ranging from 18/32" to 19/32". All-steel construction and scrub-resistant compounding combine to help with last mile delivery. The ASD meets 3PMSF requirements.



### WORK SERIES™ RHT 2

The Cooper® WORK Series™ RHT 2 is a SmartWay® verified regional trailer tire that has tread depths ranging from 16/32" to 18/32". The RHT 2 utilizes scrub guard technology and compounding to help resist cuts and chips. This tire is built for both tandem and spread-axle trailers.



## WORK SERIES™ RHA 2

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-034-018	295/75R22.5	H/16	149/146L	75 mph	(8.25) 8.25-9.00	125	7,160	6,610	40.22	11.18	18.9	13.2	516	20.0	25	9.3	120
				120 km/h		850	3,000	1,022	284	479	335	321	16.4	638	235	53.9	
172-033-018	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	5,840	41.54	10.74	19.4	12.5	500	20.0	26	9.1	121
				120 km/h		830	3,000	2,650	1,055	273	493	318	311	16.4	660	232	54.7
172-018-018	285/75R24.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	41.56	11.18	19.6	12.5	500	20.0	25	9.3	122
				120 km/h		760	2,800	2,575	1,056	284	497	318	311	16.4	638	235	55.2
172-036-018	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.50	10.72	20.4	12.5	478	20.0	26	9.1	129
				120 km/h		830	3,250	3,000	1,105	272	518	318	297	16.4	660	232	58.2

## WORK SERIES™ RHA

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-001-009	255/70R22.5	H/16	140/137L	75 mph	(8.25) 6.75-8.25	120	5,510	5,070	36.85	10.2	17.17	11.6	563	18.0	28	8.3	91
				120 km/h		830	2,500	2,300	936	258	436	295	350	14.3	711	210	41.2
172-017-009	295/75R22.5	H/16	149/146L	75 mph	(8.25) 8.25-9.00	125	7,160	6,610	40.39	11.1	18.86	12.9	513	22.5	30	8.9	115
				120 km/h		850	3,250	3,000	1,026	283	479	327	319	18.0	762	225	52.1
172-011-009	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.69	11.3	19.41	12.5	497	22.5	26	8.9	122
				120 km/h		830	3,000	2,725	1,059	286	493	318	309	18.0	660	225	55.4
172-016-009	285/75R24.5	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	41.69	10.8	19.57	12.5	497	22.5	30	8.9	118
				120 km/h		760	2,800	2,575	1,059	274	497	318	309	18.0	762	225	53.7
172-009-009	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.58	11.1	20.35	12.5	476	22.5	26	8.9	129
				120 km/h		830	3,250	3,000	1,107	281	517	318	296	18.0	660	225	58.4

## WORK SERIES™ ASA

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-024-012	225/70R19.5	G/14	128/126N	87 mph	(6.75) 6.00-6.75	110	3,970	3,750	32.17	9.0	14.96	10.0	645	17.0	28	7.6	66
				140 km/h		760	1,800	1,700	817	229	380	254	401	13.4	711	193	30.1
172-025-012	245/70R19.5	H/16	136/134M	81 mph	(7.50) 6.75-7.50	120	4,940	4,675	33.23	10.0	15.39	11.0	624	17.0	26	8.4	72
				130 km/h		825	2,240	2,120	844	255	391	279	388	13.4	660	213	32.9

## WORK SERIES™ AWD

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-011	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	40.79	11.4	19.02	12.9	508	26.0	28	9.8	121
				120 km/h		760	2,800	2,575	1,036	289	483	327	316	20.8	711	248	55.0
172-011-011	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.97	11.2	19.53	12.5	494	26.0	28	9.8	127
				120 km/h		830	3,000	2,725	1,066	285	496	318	307	20.8	711	248	57.9
172-009-011	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	44.29	11.2	20.67	12.5	468	26.0	28	9.8	137
				120 km/h		830	3,250	3,000	1,125	284	525	318	291	20.8	711	248	62.4

## WORK SERIES™ RHD

M+S SMARTWAY®

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-005	295/75R22.5*	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	40.75	11.1	19.02	12.9	509	26.0	28	9.0	116
				120 km/h		760	2,800	2,575	1,035	281	483	327	316	20.7	711	229	52.9
172-011-005	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.97	11.3	19.53	12.5	494	26.0	26	8.6	121
				120 km/h		830	3,000	2,725	1,066	288	496	318	307	20.7	660	218	55.0
172-018-005	285/75R24.5*	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	41.97	10.8	19.69	12.5	494	26.0	28	9.0	122
				120 km/h		760	2,800	2,575	1,066	274	500	318	307	20.7	711	229	55.3
172-009-005	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.94	11.1	20.51	12.5	472	26.0	26	8.6	131
				120 km/h		830	3,250	3,000	1,116	281	521	318	293	20.7	660	218	59.3

# COOPER® WORK SERIES™

## REGIONAL HAUL APPLICATION

GET TO WORK

### WORK SERIES™ ASD

M+S

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-024-013	225/70R19.5	G/14	128/126N	87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.20 818	9.1 230	15.00 381	10.0 254	644 400	18.0 14.3	18 457	7.2 184	64 29.1
172-025-013	245/70R19.5	H/16	136/134M	81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.35 847	10.0 255	15.47 393	11.0 279	622 386	19.0 15.2	22 559	8.0 203	72 32.6

### WORK SERIES™ RHT 2

\*SMARTWAY®

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-007-015	215/75R17.5	H/16	135/133L	75 mph 120 km/h	(6.00) 6.00-6.75	123 848	4,805 2,180	4,540 2,060	30.51 775	8.5 216	14.29 363	9.4 239	680 422	16.0 12.7	18 457	7.1 181	59 26.9
172-050-015	245/70R17.5	J/18	143/141K	68 mph 110 km/h	(7.50) 6.75-7.50	127 875	6,005 2,725	5,675 2,575	31.30 795	9.6 243	14.49 368	11.0 279	662 412	16.0 12.7	22 559	8.5 216	69 31.4
172-001-015	255/70R22.5	H/16	140/137L	75 mph 120 km/h	6.75-8.25	120 830	5,510 2,500	5,070 2,300	36.69 932	10.3 262	17.09 434	11.3 287	565 351	16.0 12.7	28 711	8.3 210	90 40.8
172-049-015	275/70R22.5	J/18	148/145L	75 mph 120 km/h	(8.25) 7.50-8.25	130 900	6,940 3,150	6,395 2,900	38.07 967	11.0 279	17.68 449	12.2 311	545 338	18.0 14.3	28 711	9.0 229	105 47.9
172-047-015	295/75R22.5*	G/14	144/141L	75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	39.92 1,014	11.1 281	18.66 474	13.2 335	519 323	16.0 12.7	28 711	8.5 216	106 48.2
172-046-015	11R22.5*	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.22 1,047	11.3 287	19.21 488	12.5 318	503 313	16.0 12.7	24 610	8.5 216	111 50.3
172-009-015	11R24.5*	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.31 1,100	11.1 282	20.24 514	12.5 318	479 297	16.0 12.7	24 610	8.5 216	122 55.4

For complete product and warranty details, please visit [www.coopertrucktires.com](http://www.coopertrucktires.com).

## VERIFICATIONS, CLASSIFICATIONS AND FEATURES



**Low Cost of Ownership™** PRO and WORK Series tires help provide a balance of fuel efficiency and tread wear, all built around a durable casing designed for retreadability.



**Energy Conservation Optimization™ (ECO)** tires offer low rolling resistance, which helps provide increased fuel economy.



The **Final Mile™** lineup helps withstand the rigors associated with urban delivery while helping deliver all-season traction, scrubbing and curbing.



**SmartWay® Verified** tires meet the program's low-rolling resistance criteria – helping to reduce fuel consumption, thereby reducing fuel costs and benefiting the environment.



**Three-Peak Mountain Snowflake (3PMSF)** designation indicates the tires meet the required industry standards for traction.



**Scrub Guard™** technology features proprietary compounds and tread designs to help minimize impacts from frequent start/stops, tight turns and curb scrubbing.



**Chip Guard™** technology features proprietary compounds and tread patterns to help minimize the impact of off-road conditions.



**Snow Groove™** technology uses saw-tooth grooves to help provide enhanced grip through snow-on-snow traction. Products with this technology often feature 3PMSF designation.

WEAR SQUARE™



The **Wear Square™** visual indicator helps you determine the remaining tread on your tires and can assist in detecting wheel alignment issues with your vehicle.