

COOPER® PRO SERIES™

LONG HAUL APPLICATION

RUN WITH THE PROS

The **COOPER® PRO SERIES™** tires are an on-highway, long haul lineup featuring proprietary technology and are SmartWay® verified.

PRO SERIES™ LHS 2

The Cooper® PRO Series™ LHS 2 tire is Cooper's steer tire for over-the-road applications. With a tread depth of 18/32", the Cooper PRO Series Long Haul Steer 2 tire is fuel efficient and combines an innovative compound with wide casing dimensions, a wide footprint and a NEW patent-pending decoupling rib design to help deliver long, even wear.



SmartWay®
VERIFIED



PRO SERIES™ LHD

The Cooper® PRO Series™ LHD tire is a fuel-efficient long haul drive tire with wide casing dimensions and a 30/32" tread depth that helps deliver long miles to removal.



SmartWay®
VERIFIED



PRO SERIES™ LHT

The Cooper® PRO Series™ LHT tire is a fuel-efficient trailer tire designed for long haul applications. Featuring a 12/32" tread depth, the SmartWay verified LHT utilizes a fuel-efficient compound and a casing that helps deliver retreadability.



SmartWay®
VERIFIED



SCAN TO
DOWNLOAD



COOPER
TIRES

COMMERCIAL SERIES
PRO WORK SEVERE

COOPER® PRO SERIES™

LONG HAUL APPLICATION

RUN WITH THE PROS

PRO SERIES™ LHS 2

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-017-002	295/75R22.5	H/16	149/146L	75 mph 120 km/h	(8.25) 8.25-9.00	125 850	7,160 3,250	6,610 3,000	40.20 1,021	11.3 287	18.78 477	12.9 327	516 320	18.0 14.3	24 610	9.3 235	115 52.4
172-011-002	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.73 1,060	11.1 283	19.41 493	12.5 318	497 309	18.0 14.3	24 610	9.3 235	118 53.7
172-023-002	285/75R24.5	H/16	147/144L	75 mph 120 km/h	(8.25) 7.50-9.00	120 830	6,780 3,075	6,175 2,800	41.38 1,051	10.9 278	19.41 493	12.5 318	501 311	18.0 14.3	26 660	9.3 235	120 54.3
172-009-002	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.74 1,111	11.0 280	20.43 519	12.5 318	474 295	18.0 14.3	24 610	9.3 235	129 58.6

PRO SERIES™ LHD

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-003	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.94 1,040	11.4 289	19.09 485	12.9 327	506 315	30.0 23.7	28 711	9.6 245	130 58.9
172-011-003	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	42.17 1,071	11.5 293	19.61 498	12.5 318	492 306	30.0 23.7	26 660	9.8 248	136 61.6
172-018-003	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	42.20 1,072	10.7 273	19.76 502	12.5 318	491 305	30.0 23.7	28 711	9.5 241	135 61.4
172-009-003	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	44.13 1,121	11.4 289	20.59 523	12.5 318	470 292	30.0 23.7	26 660	9.8 248	145 66.0

PRO SERIES™ LHT

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-004	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	39.69 1,008	11.3 288	18.54 471	12.9 327	522 325	12.0 9.5	26 660	8.7 222	102 46.2
172-004-004	11R22.5	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.38 1,051	11.1 282	19.29 490	12.5 318	501 311	12.0 9.5	24 610	8.8 224	108 48.9
172-018-004	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.06 1,043	10.9 276	19.29 490	12.5 318	505 314	12.0 9.5	26 660	8.8 224	110 49.8
172-006-004	11R24.5	G/14	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.43 1,103	11.0 280	20.28 515	12.5 318	477 297	12.0 9.5	24 610	8.5 216	116 52.5

For complete product and warranty details, please visit www.coopertrucktires.com.

VERIFICATIONS, CLASSIFICATIONS AND FEATURES



Low Cost of Ownership™ PRO and WORK Series tires help provide a balance of fuel efficiency and tread wear, all built around a durable casing designed for retreadability.



SmartWay® Verified tires meet the program's low-rolling resistance criteria – helping to reduce fuel consumption, thereby reducing fuel costs and benefiting the environment.



Energy Conservation Optimization™ (ECO) tires offer low rolling resistance, which helps provide increased fuel economy.



The **Wear Square™** visual indicator helps you determine the remaining tread on your tires and can assist in detecting wheel alignment issues with your vehicle.

BETTER FUTURE If possible, steer clear of printing this piece
Digital materials available at coopertrucktires.com/resources



**COOPER
TIRES**

**COMMERCIAL SERIES
PRO WORK SEVERE**