



# Work Series™ RHA 2 Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Inflation Pressure	Dual Max Load	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Section Width	Overall Width Loaded
295/75R22.5	H	516 /mi	119.7 lbs	7160 lbs	125 psi	6610 lbs	18.9 in	20	75 mph	(8.25 )8.25-9.00 in	40.22 in	11.18 in	-
		321 /km	53.9 kgs	3000 kgs	850 kPa	3000 kgs	479 mm	16.4 mm	120 kph		1021.59 mm	283.97 mm	-
11R22.5	H	500 /mi	121.4 lbs	6610 lbs	120 psi	5840 lbs	19.4 in	20	75 mph	(8.25) 7.50-8.25 in	41.54 in	10.74 in	-
		311 /km	54.7 kgs	3000 kgs	830 kPa	2650 kgs	492 mm	16.4 mm	120 kph		1055.12 mm	272.80 mm	-
11R24.5	H	478 /mi	129.2 lbs	7160 lbs	120 psi	6610 lbs	20.4 in	20	75 mph	(8.25) 7.50-8.25 in	43.5 in	10.72 in	-
		297 /km	58.2 kgs	3250 kgs	830 kPa	3000 kgs	518 mm	16.4 mm	120 kph		1104.90 mm	272.29 mm	-
285/75R24.5	G	500 /mi	122.4 lbs	6175 lbs	110 psi	5675 lbs	19.6 in	20	75 mph	(8.25 )8.25-9.00 in	41.56 in	11.18 in	-
		292 /km	55.2 kgs	2800 kgs	760 kPa	2575 kgs	497mm	16.4 mm	120 kph		1055.62 mm	283.97 mm	-